

Date of issue: October 1994.

Page 1

Company:	CUFADAN A/S Hammerholmen 20 DK-2650 Hvidovre Denmark Telephone: (45) 36 77 36 87	Distributor:	AB PLANTESERVICE Helgesvej 17 DK-4200 Slagelse Denmark Telephone: (45) 58 50 00 61
Commercial product name:	FLAMOL A		
Chemical characterization:	Water-based fireproofing liquid to untreated wood.		
Form:	Liquid.		
Colour:	Yellowish.		
Odour:	-		
Physical and safety data:			
Change in physical state:	-		
Density:	Approx. 1.1 g/cm ³		
Vapour pressure:	-		
Viscosity:	-		
Solubility in water:	Soluble.		
pH value:	Approx. 7		
Flash point:	-		
Ignition temperature:	-		
Explosive limits:	-		
Thermal decomposition:	-		
Hazardous decomposition products:	No hazardous decomposition products when stored and handled correctly.		
Hazardous reactions:	-		
Further information:	-		
Transport:	Not dangerous cargo.		
Regulations:	No labelling is required.		
Protective measures, storage and handling:			
Technical protective measures:	-		
Personal protective equipment:	Protective goggles are recommended when an atomizer is used.		
Industrial hygiene:	Wash hands before breaks and end of work.		
Protection against fire and explosion:	The product cannot be burnt.		
Disposal:	Follow the local regulations.		
Measures in case of accidents and fires:			
After spillage/leakage/gas leakage:	Remove the spillage mechanically with absorbent materials (e.g. saw dust, floor cloth etc.).		
Extinguishing media:	The product cannot be burnt.		
First aid:	In case of eye contact rinse carefully and thoroughly with water and seek medical advice. In case of skin contact wash with soap and plenty of water. Moisturizer is recommended. In case of swallowing drink plenty of water and seek medical advice.		
Further information:	-		
Information on toxicity:	-		
Information on ecological effects:	-		
Further information:	None.		

The data given here is based on current knowledge and does not signify any warranty with regard to the product's properties.